

# Residual Current Circuit Breaker (RCCBs)

## Residual Current - Operated Devices with Overcurrent protection (RCBOs)

### System Pro M



Models	RCCBs				RCBOs			
	FH202	FH204	F202	F204	DS201	DSE201	DS271	DS203NC
<b>Standards</b>	IEC/EN 61008				IEC/EN 61009			
<b>Electrical Features</b>								
<b>Pole</b>	2P	4P	2P	4P	1P+N	1P	1P	1P
Rated Current In [A]	25, 40, 63		80, 100		10, 16, 20, 25	6, 10, 16, 20, 25, 32	6, 10, 16, 20, 25, 32, 40	6, 10, 16, 20, 25, 32
Rated breaking capacity acc. To IEC/EN 61009 Icn [kA]	6**		10*		6	6	10	6
Rated sensitivity [mA]	30, 100***, 300***				30	30	30	30
Rated Voltage Ue [V]	230/400 - 240/415				230-240			400-415
<b>Mechanical Features</b>								
Electrical life	10000				10000			
Mechanical life	20000				20000			
Terminal size top / bottom per cable	25/25				25/25	16/16		25/25
<b>ราคาต่อหน่วย - บาท</b>								
<b>RCCBs and RCBOs 30 mA (ป้องกันไฟดูด ไฟรั่ว)</b>								
6 [A]					3,790	2,525	3,160	7,500
10, 16, 20 [A]					3,790	2,525	3,160	7,500
25 [A]	2,145	3,685	***	***	3,790	2,600	3,370	7,500
32 [A]					3,790	2,600	3,370	7,500
40 [A]	2,530	4,100	***	***	3,790		3,370	
63 [A]	4,000	6,000	***	***				
80 [A]			5,370	7,050				
100 [A]			6,420	8,630				
<b>ราคาอุปกรณ์เสริม - บาท (Accessories)</b>								
<b>Auxiliary contacts</b>								
Signal contact/auxiliary switch	S 2 C-S/H6R	-		1,055	1,055	-		***
Terminal insulated	SZ-Ast 50 I	-		420	420	-		***
Terminal insulated	SZ-Ast 55 I	-		420	420	-		***

\* Require fuse backup 100A gL type

\*\* Require fuse backup 63A gL type

\*\*\* กรุณาสอบถามรายละเอียดเพิ่มเติม